BRL
1310
c.2A

BRL R 1310

BRL

AD 630781

REPORT NO. 1310

ERROR STUDY OF A WORLDWIDE SATELLITE TRIANGULATION NET

by

Edna L. Lortie

January 1966

Distribution of this document is unlimited.

U. S. ARMY MATERIEL COMMAND
BALLISTIC RESEARCH LABORATORIES
ABERDEEN PROVING GROUND, MARYLAND

Destroy this report when it is no longer needed.
Do not return it to the originator.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

B A L L I S T I C R E S E A R C H L A B O R A T O R I E S

REPORT NO. 1310

JANUARY 1966

Distribution of this document is unlimited.

ERROR STUDY OF A WORLDWIDE SATELLITE TRIANGULATION NET

Edna L. Lortie

Ballistic Measurements Laboratory

RDT & E Project No. 1L013001A91A

A B E R D E E N P R O V I N G G R O U N D, M A R Y L A N D

B A L L I S T I C R E S E A R C H L A B O R A T O R I E S

REPORT NO. 1310

ELLortie
Aberdeen Proving Ground, Md.
January 1966

ERROR STUDY OF A WORLDWIDE SATELLITE TRIANGULATION NET

ABSTRACT

A proposed three-dimensional geodetic reference system, consisting of 36 stations so situated on the surface of the earth as to form a closed system of approximate equilateral triangles surrounding the globe, is studied in an attempt to find out to what degree of accuracy the station positions can be determined when triangulating the corresponding station coordinates by photogrammetric techniques. The polyhedron of the spatially oriented triangles is formed by photographing a high altitude satellite against the star background. The triangulation method depends on applying analytical photogrammetric techniques to satellite observations where the satellite serves as a high altitude auxiliary triangulation target point. Numerical analyses on the whole net and portions of it are presented from which the problem of error propagation and the influence of the number of baselines can be studied.

TABLE OF CONTENTS

		Page
	ABSTRACT	3
I.	INTRODUCTION	7
II.	DISCUSSION OF ANALYTICAL APPROACH	13
III.	DISCUSSION OF RESULTS	28
	REFERENCES	72
	DISTRIBUTION LIST	73

I. INTRODUCTION

The use of artificial satellites in scientific research provides geodesy for the first time in its history with a means to create a three-dimensional worldwide reference system without referring to the direction of gravity. Many of the basic difficulties encountered in a classic geodetic triangulation will be eliminated when photogrammetric methods are applied to satellite observations. A satellite triangulation can be used for establishing a worldwide three-dimensional geodetic reference system which, without referring to gravity, is entirely geometrically defined.[1*] The system will consist of stations on the physical surface of the earth, located in such a way as to form a closed system of as near as possible equilateral triangles encompassing the globe. These stations will serve as a reference frame to which can be tied both geometrically-oriented mapping programs and the evaluation of satellite orbits for determining gravitational and related geo-physical parameters.[2]

Coast and Geodetic Survey gave considerable thought to the requirements in planning a worldwide triangulation system. This organization has the technical responsibility for the execution of a worldwide satellite triangulation program. Their conclusions concerning a useful satellite orbit are summarized below.[3-4]

First, the line of sight to the satellite must be at least 30° above the horizon in order to avoid disturbing refraction anomalies.

Second, the maximum angle between any two planes generating the spatial direction between two stations must be at least 60° in order to provide sufficient geometrical strength for the determination of three-dimensional station positions.

Third, the distance to the satellite should be about the same as that between any two stations, so that the scale does not contribute an unproportional amount of error.

---

* *Superscript numbers denote references which may be found on page 72.*

A nominal polar orbit is necessary because the satellite must pass over every geographical position. Furthermore, a nominal circular orbit is required in order that changes in altitude are minimized. A near optimum scheme was found which consists of thirty-six stations. Table I is a list of the names and geographical locations of the thirty-six stations, which make up the proposed worldwide satellite triangulation net. Figures 1, 2 and 3 show details of the thirty-six station net arrangement on the globe.

An error analysis of the proposed thirty-six station net is conducted to determine with what accuracy the station positions can be obtained by satellite triangulation. The reference system with respect to which individual satellite directions are determined is the right ascension and declination system. The triangulation is accomplished by photographing a high altitude satellite against the star background simultaneously from at least two ground stations.[5]

TABLE I

PROPOSED WORLDWIDE SATELLITE TRIANGULATION NET

No.	Station Name	Latitude	Longitude
1	Greenland, Thule A.F.B.	76.5° N	68.7° W
2	U.S.A., Aberdeen, Md.	39.5 N	76.1 W
3	U.S.A., Larson A.F.B., Wash.	47.2 N	119.3 W
4	U.S.A., Aleutian Is., Shemya I.	52.7 N	174.1 E
5	U.S.S.R., Tura, Siberia	64.8 N	101.0 E
6	Finland, Kuopio	62.7 N	28.0 E
7	Azores Is., Pico I.	39.0 N	28.5 W
8	Dutch Guiana, Paramaribo	05.5 N	55.2 W
9	Equador, Quito	00.1 S	78.5 W
10	Clipperton Island	10.3 N	109.2 W
11	U.S.A., Hilo, Hawaii	19.8 N	155.0 W
12	Wake Island	19.7 N	166.2 E
13	Japan, Kagoshima	31.7 N	130.6 E
14	India, Gauhati	26.2 N	91.7 E
15	Iran, Sabzevār	36.5 N	57.5 E
16	Libya, Sirte	31.7 N	16.4 E
17	Liberia, Roberts Field	06.8 N	10.2 W
18	Trindade Island	20.5 S	29.4 W
19	Argentina, Villa Dolores	32.0 S	65.1 W
20	Sala-Y-Gomez Island	26.6 S	105.2 W
21	Pukapuka Island	14.7 S	138.8 W
22	Wallis Is., Uveá I.	13.2 S	176.3 W
23	New Guinea, Kikori	07.3 S	144.2 E
24	Sumatra, Palembang	03.0 S	105.0 E
25	Maldive Is., Male	04.2 N	73.3 E
26	Sudan, Juba	04.8 N	31.6 E
27	Southwest Africa, Bogenfels	27.8 S	15.8 E
28	So. Sandwich Is., Saunders I.	58.4 S	26.7 W
29	Antarctica, Peter I.	69.2 S	90.0 W
30	So. Pacific Ocean, Shoal	41.5 S	148.6 W
31	New Zealand, Queenstown	45.0 S	168.2 E
32	Australia, Denmark	35.0 S	117.3 E
33	St. Paul Island	38.7 S	77.0 E
34	Madagascar, Fort Dauphin	25.0 S	47.1 E
35	Antarctica, U.S.S.R. Station	68.0 S	46.4 E
36	Antarctica, France Station	67.0 S	139.0 E


0°
033
028
035
90°E
019
ANTARCTICA
80°
70°
60°
50°
40°
SOUTH AMERICA
032
029
036
90°W
AUSTRALIA
031
NEW
ZEALAND
180°

FIGURE 1


90°E
U.S.S.R.
005
006
0°
80°
GREENLAND
001
004
007
70°
180°
60°
ALASKA
50°
CANADA
003
002
90° W

FIGURE 2


GEOMETRIC SATELLITE NETWORK
NORTH PACIFIC OCEAN
NORTH ATLANTIC OCEAN
INDIAN OCEAN
SOUTH PACIFIC OCEAN
SOUTH ATLANTIC OCEAN
INDIAN OCEAN
ANTARCTIC OCEAN
QUEEN MAUD LAND

FIGURE 3

II. DISCUSSION OF ANALYTICAL APPROACH

A brief description of the method used to determine the propagation of errors over the net will show how the direction to each satellite point is incorporated in the final least squares adjustment. It is assumed the reader is familiar with the theory developed in Ballistic Research Laboratories Report No. 1065.[5]

Applying this theory the following is assumed.

1. Each line of sight belonging to a specific satellite point is imaged at the center of the corresponding photograph, i.e.,

$$l_x = l_y = 0, \quad x_p = y_p = 0 \quad \text{and} \quad k_1 = k_2 = k_3 = 0$$

2. $\kappa = 0$

Enforcing the orientation parameters α and ω as are determined in practice from the photographed stars, there remains only the station coordinates X_0, Y_0, Z_0 and the satellite coordinates X, Y, Z which must be determined by a least squares adjustment.

Equation(3)[5] which expresses the functional relation that exists for an individual ray can now be expressed by the corresponding observation equation of the form

$$f(V_j) = F(O_i, X_j)$$

where O_i refers to the parameters X_0, Y_0, Z_0 for a certain camera station i and X_j refers to the station location X, Y, Z of any one individual satellite point j.

It is assumed that each satellite point j is observed from either two or three stations, whereby satellites in the center of a triangle are seen from three stations while those on the center of station lines are observed from just two stations.

Since we are interested only in station positions, for computational convenience all satellite positions are eliminated. To accomplish this, it is necessary at the time of elimination that all rays to a specific satellite position have been incorporated. From the geometrical standpoint no one ray has preference over another, therefore each ray may be treated independently. It is necessary to consider only one set of two equations for any individual ray and apply the same computation to all rays one after the other.

The equation which simulates mathematically a single ray is the condition that object point, center of projection and corresponding image point are collinear.

In this case, therefore, we obtain for each ray two equations:

$$v_x = - D_X\Delta X - E_X\Delta Y - F_X\Delta Z + D_X\Delta X_0 + E_X\Delta Y_0 + F_X\Delta Z_0$$

$$v_y = - D_Y\Delta X - E_Y\Delta Y - F_Y\Delta Z + D_Y\Delta X_0 + E_Y\Delta Y_0 + F_Y\Delta Z_0$$

In matrix notation we obtain the B matrices, namely

B_0 matrix for the stations $\begin{vmatrix} -D_X & -E_X & -F_X \\ -D_Y & -E_Y & -F_Y \end{vmatrix}$

and

B_X matrix for satellite positions $\begin{vmatrix} D_X & E_X & F_X \\ D_Y & F_Y & F_Y \end{vmatrix}$

From Figure (4)

$$(X) = X - X_0$$

$$(Y) = Y - Y_0$$

$$(Z) = Z - Z_0$$

$$q = \sqrt{(X)^2 + (Y)^2 + (Z)^2}$$

c = focal length = constant





$(X) = X_S - X_O$

$(Y) = Y_S - Y_O$

$(Z) = Z_S - Z_O$

O = center of projection

FIGURE 4

$$\sin\alpha = \frac{(X)}{\sqrt{(X)^2 + (Z)^2}} \qquad \sin\omega = \frac{(Y)}{\sqrt{(X)^2 + (Y)^2 + (Z)^2}}$$

$$\cos\alpha = \frac{(Z)}{\sqrt{(X)^2 + (Z)^2}} \qquad \cos\omega = \frac{\sqrt{(X)^2 + (Z)^2}}{\sqrt{(X)^2 + (Y)^2 + (Z)^2}}$$

Since $\kappa = 0$ the direction cosines[5] become:

$A_1 = -\cos\alpha$ $\qquad B_1 = 0$ $\qquad C_1 = \sin\alpha$

$A_2 = -\sin\alpha\cos\omega$ $\qquad B_2 = \cos\omega$ $\qquad C_2 = -\cos\alpha\sin\omega$

$D = \sin\alpha\cos\omega$ $\qquad E = \sin\omega$ $\qquad F = \cos\alpha\cos\omega$

and thus the computational auxiliaries are:

(1) $= 0$ $\qquad$ (4) $= -B_1$ $\qquad$ (7) $= -B_2$

(2) $= 0$ $\qquad$ (5) $= -C_1$ $\qquad$ (8) $= -C_2$

(3) $= -A_1$ $\qquad$ (6) $= -A_2$ $\qquad$ (9) $= 0$

By substitution, the coefficients of the observation equations are found to be:

$$D_X = \frac{c}{q} \frac{(Z)}{\sqrt{(X)^2 + (Z)^2}} \qquad D_Y = \frac{c}{q^2} \frac{(X)(Y)}{\sqrt{(X)^2 + (Z)^2}}$$

$$E_X = 0 \qquad E_Y = \frac{-c}{q^2} \sqrt{(X)^2 + (Z)^2}$$

$$F_X = -\frac{c}{q} \frac{(X)}{\sqrt{(X)^2 + (Z)^2}} \qquad F_Y = \frac{c}{q^2} \frac{(Y)(Z)}{\sqrt{(X)^2 + (Z)^2}}$$

To form the normal equations we must compute for each ray the following expressions:

$$\left[DD\right] = D_X^2 + D_Y^2 = \frac{c^2}{q^4}\left[(Y)^2 + (Z)^2\right]$$

$$\left[DE\right] = D_X E_X + D_Y E_Y = -\frac{c^2(X)(Y)}{q^4}$$

$$\left[DF\right] = D_X F_X + D_Y F_Y = -\frac{c^2(X)(Z)}{q^4}$$

$$\left[EE\right] = E_X^2 + F_Y^2 = \frac{c^2}{q^4}\left[(X)^2 + (Z)^2\right]$$

$$\left[EF\right] = E_X F_X + E_Y F_Y = -\frac{c^2}{q^4}(Y)(Z)$$

$$\left[FF\right] = F_X^2 + F_Y^2 = \frac{c^2}{q^4}\left[(X)^2 + (Y)^2\right]$$

Since each ray is treated independently it will contribute to the normal equation system the following submatrix:

	Satellite			Station		
	ΔX_s	ΔY_s	ΔZ_s	ΔX_0	ΔY_0	ΔZ_0
Satellite	[DD]	[DE]	[DF]	[-DD]	[-DE]	[-DF]
	[DE]	[EE]	[EF]	[-DE]	[-EE]	[-EF]
	[DF]	[EF]	[FF]	[-DF]	[-EF]	[-FF]
Station	[-DD]	[-DE]	[-DF]	[DD]	[DE]	[DF]
	[-DE]	[-EE]	[-EF]	[DE]	[EE]	[EF]
	[-DF]	[-EF]	[-FF]	[DF]	[EF]	[FF]

$=$

B_1	$-B_1$
$-B_1$	B_1

Figure 5

Figure 5 shows the 6x6 submatrix for one ray only. A satellite will never be seen from more than three stations so this 6x6 submatrix will be computed a maximum of three times, once for each satellite ray. If the satellite is observed from only two stations, the third 6x6 submatrix will appear as a null matrix.

For each individual observation we are able to form a corresponding partial normal equation system, and by adding each additional ray, the final normal equation system can be accumulated as shown in Figures 6, ABCD.

At this point in the computational procedure the satellite point is eliminated completely.

In general $$D = B_0 - B_{X/0}^T B_X^{-1} B_{X/0}$$

	12			
12	B_1	$-B_1$		
	$-B_1$	B_1		

FIGURE 6A

Figure 6A represents the contribution of one ray to the normal equation system.

	12			
12	B_1+B_2	$-B_1$	$-B_2$	
	$-B_1$	B_1		
	$-B_2$		B_2	

FIGURE 6B

Figure 6B represents the contribution of two rays to the normal equation system.

	12			
12	$B_1+B_2+B_3$	$-B_1$	$-B_2$	$-B_3$
	$-B_1$	B_1		
	$-B_2$		B_2	
	$-B_3$			B_3

FIGURE 6C

Figure 6C represents the contribution of all three rays to the normal equation system.

	12	
12	B_X	$B_{X/0}$
	$B^T_{X/0}$	B_0

FIGURE 6D

The upper left 3 x 3 B_X-matrix contains coefficients associated with the unknown corrections of the satellite point, ΔX, ΔY, and ΔZ.

The lower right 9 x 9 B_0-matrix is subdivided into three block diagonal matrices, one for each camera station that sees the satellite point, and is associated with the corrections of the unknown positional parameters ΔX_0, ΔY_0, and ΔZ_0 for each station.

The $B_{X/0}$-matrix contains the coefficients which represent the geometrical fact that the satellite point was seen from stations shown in the B_0-matrix.

This elimination cycle reduces the 12x12 matrix of Figure 6D to a 9x9 D-matrix as shown by Figure 7, concerned with station data only.

	Sta. i			Sta. j			Sta. k		
	ΔX_0	ΔY_0	ΔZ_0	ΔX_0	ΔY_0	ΔZ_0	ΔX_0	ΔY_0	ΔZ_0
Station i	D_{ii}			D_{ij}			D_{ik}		
Station j	D_{ij}			D_{jj}			D_{jk}		
Station k	D_{ik}			D_{jk}			D_{kk}		

Figure 7

In Figure 7 the satellite point has been numerically eliminated, and only station unknowns ΔX_0, ΔY_0, and ΔZ_0 remain for two or three stations depending on how many stations recorded the specific satellite point.

This study is made for a maximum of thirty-six stations where n denotes the number of ground stations included in a specific net. The size of the reduced normal equation system will be a 3nx3n matrix containing unknown ground stations only.

Consequently, each 9x9 D-matrix is partitioned into nine 3x3 submatrices, each of which is added in its proper position within the final 3nx3n matrix system as shown in Figure 8.

Before the resulting system is inverted, the following additional conditions must be incorporated:

1) The geometric condition that sets the sum of all adjusted X_0, Y_0, Z_0 coordinates individually equal to zero in order to obtain a symmetrically arranged error distribution field.

Assume one satellite point is observed from stations 3, 5, and 7.

The 9 x 9 D-matrix is sub-divided and added into the 3n x 3n system (n = 7) as follows:

$$i = 3$$
$$j = 5$$
$$K = 7$$



FIGURE 8

$$\sum \Delta X_O = -\sum X_O$$

$$\sum \Delta Y_O = -\sum Y_O$$

$$\sum \Delta Z_O = -\sum Z_O$$

2) Metric condition: At least one scalar must be introduced. Allowance has been made in the computer program to incorporate as many as four scalars with their respective variances.

If the distance between two stations (i and j) is enforced, the corresponding metric conditional equation is introduced:

$$G \cdot \Delta X_{O_i} + H \cdot \Delta Y_{O_i} + J \cdot \Delta Z_{O_i} - G \cdot \Delta X_{O_i} - H \cdot \Delta Y_{O_i} - J \cdot \Delta Z_{O_i} = 0$$

where

$$G = (X_{O_i} - X_{O_j})/d_{ij}$$

$$H = (Y_{O_i} - Y_{O_j})/d_{ij}$$

$$J = (Z_{O_i} - Z_{O_j})/d_{ij}$$

$$d_{ij} = \sqrt{(X_{O_i} - X_{O_j})^2 + (Y_{O_i} - Y_{O_j})^2 + (Z_{O_i} - Z_{O_j})^2}$$

These conditions are incorporated in the final normal equation system by simply adding the specific equations to the normal equation system (3nx3n) and at the same time restoring the system to a quadratic form. (page 33)[5].

Assuming n=36 and the number of scalars introduced to be four, Figure 9 shows the resulting system after the geometric and metric conditions have been incorporated. A system of this size refers to



FIGURE 9

FINAL MATRIX TO BE INVERTED

108 station coordinates and requires the inversion of a 115x115 matrix. The inverted Q-matrix refers to the Cartesian coordinate system in which the triangulation was performed with its origin at the center of gravity of the whole system.

$$Q = \begin{vmatrix} Q_{X_{O_1}} & & & & & & \\ & Q_{Y_{O_1}} & & & & & \\ & & Q_{Z_{O_1}} & & & & \\ & & & Q_{X_{O_2}} & & & \\ & & & & \cdot & & \\ & & & & & \cdot & \\ & & & & & & \cdot \\ & & & & & & Q_{Z_{O_n}} \end{vmatrix}$$

The diagonal terms can be used to compute the mean errors of the station coordinates $m_{X_{O_1}}, m_{Y_{O_1}}, m_{Z_{O_1}} \cdots m_{Z_{O_n}}$ with

$$m_{X_{O_i}} = \mu \cdot 10^7 \cdot \sqrt{Q_{X_{O_i}}}$$

For each station a transformation matrix T_{ϕ}, obtained from a coordinate transformation subprogram, is used to transform the diagonal terms of the Q-matrix from the Cartesian coordinate system to a geodetic ellipsoidal system, in terms of latitude (ϕ), longitude (λ) and elevation (H).[6]

Appropriate constants are applied to the diagonal terms to give results in meters.

$$m_{\phi} = K_{\phi} \cdot \mu \cdot 10^7 \qquad \text{where} \qquad K_{\phi} = 30.85 \sqrt{Q_{\phi}}$$

$$m_{\lambda} = K_{\lambda} \cdot \mu \cdot 10^7 \qquad \text{where} \qquad K_{\lambda} = 30.85 \cos \phi \sqrt{Q_{\lambda}}$$

$$m_H = K_H \cdot \mu \cdot 10^7 \qquad \text{where} \qquad K_H = \sqrt{Q_H}$$

A computer program was written at BRL in the Forast programming language which enables the investigation of error propagation for various size nets up to a maximum of 36 stations, allowing the number of scalars to vary from one to four.

An error analysis of various station schemes using hypothetical data is presented. The scheme which is thought to be most nearly ideal consists of 36 stations forming 68 triangles with 102 sides, 4000 to 4500 km in length, using a satellite altitude of 3600 km. In this scheme it was assumed that all satellite positions over the center of each of the 68 triangles were observed simultaneously from three ground stations and satellite positions over lines were observed from two stations. A total of 170 satellite positions and 408 rays were incorporated in the least squares adjustment of the 36 station net. Four specific nets are considered:

No. of stations in net	No. of triangles formed	No. of lines	No. of satellite positions observed	No. of rays incorporated in least square solution
36	68	102	170	408
35	62	96	164	390
34	56	90	158	372
28	38	66	122	282

1. In the 36 station net the stations are arranged to cover the entire earth.
2. In the 35 station net Russia is omitted.
3. In the 34 station net Russia and the South Pacific are omitted.
4. In the 28 station net the stations in the polar regions are omitted leaving a 28 station equatorial net with two rows of triangles straddling the equator.

The propagation of the errors in the station coordinates of the aforementioned triangulation nets are presented in graphical form. These results have been obtained by inverting the final normal equation system. The diagonal terms of the inverted matrix give quantitative information about the propagation of errors in the unknowns of the solution and the non-diagonal terms furnish the corresponding covariances.[5]

In all schemes the effect of a specific number (one to four) of scalars and various accuracies of these ground established baselines on the propagation of errors over the net were investigated.

The stations between which distance measurements are assumed are listed below and are indicated by scalar number on the vertical scale of Figures 10-49.

Scalar No.	Baseline	Stations between which distance measurements are assumed
1	North America	2 - 3
2	Australia	23 - 32
3	Europe	6 - 16
3*	Iran	14 - 15
4	South America	8 - 19

* For the twenty-eight station net the third scalar between stations 6 and 16 was replaced by a scalar in Iran between stations 14 and 15.

III. DISCUSSION OF RESULTS

In order to introduce the various scalars with different variances it is necessary to compute the corresponding weighting factors.[7]

Assuming a standard error of unit weight on the plate measurements of $\pm$ μ microns we have

$$P_{\ell} = 1 = \frac{K}{\mu^2 \cdot 10^{-12}} \qquad \text{or} \qquad K = \mu^2 \cdot 10^{-12}$$

Correspondingly the weight for any one introduced scalar, if its specific standard error is denoted by $\pm$ m (meters), is

$$P_X = \frac{K}{m^2} = \frac{\mu^2 \cdot 10^{-12}}{m^2}$$

Stipulating a realistic value for μ of $\pm$ 0.75 microns, $K = 0.5 \cdot 10^{-12}$ and consequently we obtain the following values for m.

P_X	m
$10^4 \cdot 10^{-14}$	assumed to be zero
$1 \cdot 10^{-14}$	$\pm$ 7 m
$0.1 \cdot 10^{-14}$	$\pm$ 20 m

For convenience the problem is scaled by 10^{14} resulting in the P_X values of 10^4, 1, and 0.1, respectively. All results are related to a focal length of the photogrammetric camera, c = 0.316m.

Figures 10, 11, 12 are concerned with the 36 station net. The accuracies are shown which can be obtained for the determination

of station coordinates. The assumed standard deviations on the baseline measurements, as outlined above, are assumed to be zero, ± 7 meters and ± 20 meters, respectively. The beneficial influence of one, two, three and four scalars on the accuracy of the determination of the station coordinates is demonstrated. The geometry of the triangulation is strengthened with each additional scalar and, consequently, the results show an improvement in the mean error of the station coordinates.

Additional scalars, even when measured with extreme accuracies, make little improvement on latitude and longitude determination. In fact, for all practical purposes one scalar is nearly as good as four. However, the height determination is decidedly improved with each additional scalar and with an increase in accuracy of scalar measurements. The ratio of the improvement in the mean error of station coordinates becomes smaller with the introduction of each additional scalar. The greatest relative improvement exists when two scalars are used to constrain the triangulation, and the addition of a third scalar will yield significant improvement. However, whether or not much is gained from four scalars over three is questionable. This fact is significant when considering the cost of obtaining baseline measurements over long distances. The influence of the measuring errors as they are propagated over the net can best be seen by examining Figure 13 which is a combined plot of Figures 10, 11, 12. Measuring errors of ± 7 meters using one baseline give about the same accuracy as four baselines with measuring errors of ± 20 meters. Similiarly, for one scalar with an assumed standard deviation of ± 20 meters the errors propagated over the net are twice as large as those obtained with the corresponding baseline measurements of ± 7 meters accuracy. The table that follows illustrates the situation. The fact should not be overlooked that only an insignificant improvement is obtained between assumed zero measurements and those with an assumed accuracy of ± 7 meters.

K_H - values for H-determination*			
No. of scalars	Assumed standard deviation of scalar		
	± 20	± 7	0
1	5.8	3.1	2.7
2	4.2	2.4	2.1
3	3.6	2.1	1.9
4	3.1	1.9	1.8

*Portions of these results were presented in [8].

The possibility of being unable to establish certain station locations led to the investigation of several other nets. The same identical runs that were computed for the 36 station net were computed for the following nets:

a) 35 station net without Russia (station No. 5 omitted) Figures 14-17.

b) 34 station net without Russia and the South Pacific (stations No. 5 and 30 omitted) Figures 18-21.

c) 28 station net without stations near the polar regions, Figures 22-25.

For each station not incorporated in the least squares adjustment the triangulation is weakened; this accounts for the more erratic appearance of each set of Figures for the 35, 34 and 28 station nets, respectively.

In the least squares adjustment for the 35 station net six triangles in the vicinity of Russia are omitted. The irregularity of Figures 14-17 for all three coordinates, latitude, longitude and height in this particular area of the net is apparent, particularly at stations which are close to the latitude and longitude of the omitted station No. 5. Station 6, which is about the same latitude as station 5, has the largest mean error in latitude over the net

while stations 13 and 14, which have longitudes near that of station 5, have the largest mean error in longitude over the net. Furthermore, the height determinations have the largest mean errors occurring on stations 6 and 14 which are closest in both latitude and longitude to station 5. On the other hand the loss in accuracy is relatively small, on account of the basic favorable error propagation, which is unique for this type of three-dimensional satellite triangulation.

In Figures 26-49 the same information is presented in a different way, by comparing the accuracies obtainable for the four different net sizes (36, 35 34 and 28 stations) in terms of latitude, longitude and height.

EDNA L. LORTIE

36 STATION NET



FIGURE 10

36 STATION NET



FIGURE 11


36 STATION NET
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
K
CONSTANT WEIGHT
WT. = 0.1
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 1 3 4 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 12

36 STATION NET



FIGURE 13


35 STATION NET
STATION NO.5 OMITTED
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
K
CONSTANT WEIGHT
WT. = 10⁴
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
m_φ = K_φ · μ · 10⁷
m_λ = K_λ · μ · 10⁷
m_H = K_H · μ · 10⁷
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 1 3 4 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 14


35 STATION NET
STATION NO.5 OMITTED
CONSTANT WEIGHT
WT. = 1.0
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
K
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
STATION NUMBER

FIGURE 15


35 STATION NET
STATION NO. 5 OMITTED
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
K
CONSTANT WEIGHT
WT. = 0.1
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 3 4 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 16


35 STATION NET
STATION NO. 5 OMITTED
VARYING WEIGHTS
• WT. = 0.1
x WT. = 1.0
• WT. = 10⁴
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
K
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED
STATION NUMBER

FIGURE 17


34 STATION NET
STATIONS NO. 5 AND 30 OMITTED
CONSTANT WEIGHT
WT. = 10^4
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
K
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
m_φ = K_φ · μ · 10^7
m_λ = K_λ · μ · 10^7
m_H = K_H · μ · 10^7
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 1 3 4 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 18


34 STATION NET
STATIONS NO. 5 AND 30 OMITTED
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
K
CONSTANT WEIGHT
WT. = 1.0
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 1 3 4 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 19


34 STATION NET
STATIONS NO. 5 AND 30 OMITTED
CONSTANT WEIGHT
WT. = 0.1
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
H
K
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
STATION NUMBER

FIGURE 20


34 STATION NET
STATIONS NO. 5 AND 30 OMITTED
VARYING WEIGHTS
• WT. = 0.1
x WT. = 1.0
⊙ WT. = 10⁴
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
K
H
λ
φ
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
0
10
20
30
40
STATION NUMBER
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
m_φ = K_φ · μ · 10⁷
m_λ = K_λ · μ · 10⁷
m_H = K_H · μ · 10⁷
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1
3
4
3
4
2
2

FIGURE 21


28 STATION NET
POLE CAPS OMITTED
CONSTANT WEIGHT
WT. = 10^4
VARIOUS SCALARS
1 SCALARS
2 SCALARS
3 SCALARS
4 SCALARS
K
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
mφ = Kφ·μ·10^7
mλ = Kλ·μ·10^7
mH = KH·μ·10^7
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
STATION NUMBER

FIGURE 22


28 STATION NET
POLE CAPS OMITTED
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
K
CONSTANT WEIGHT
WT. = 1.0
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H \quad K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 1 4 3 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 23


28 STATION NET
POLE CAPS OMITTED
CONSTANT WEIGHT
WT. = 0.1
VARIOUS SCALERS
1 SCALARS
2 SCALARS
3 SCALARS
4 SCALARS
K
H
λ
φ
6.6
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
$m_H = K_H \cdot \mu \cdot 10^7$
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
1 1 4 3 3 4 2 2
0 10 20 30 40
STATION NUMBER

FIGURE 24


28 STATION NET
POLE CAPS OMITTED
VARYING WEIGHTS
• WT. = 0.1
x WT. = 1.0
• WT. = 10^4
VARIOUS SCALARS
1 SCALAR
2 SCALARS
3 SCALARS
4 SCALARS
7.0
6.0
5.0
4.0
3.0
2.0
1.0
1.0
0
K
H
λ
φ
μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.
m_φ = K_φ · μ · 10^7
m_λ = K_λ · μ · 10^7
m_H = K_H · μ · 10^7
METERS
SCALARS 1-4 INTRODUCED BETWEEN STATIONS AS INDICATED.
4 3 3 4 2 2
0
10
20
30
40
STATION NUMBER

FIGURE 25

VARIOUS SIZE NETS

ONE SCALARS CONSTANT WT. = 10^4



$m_\phi = K_\phi \cdot \mu \cdot 10^7$

$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$

} METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 26

VARIOUS SIZE NETS

ONE SCALARS CONSTANT WT. = 1.0





$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 27

VARIOUS SIZE NETS

ONE SCALAR CONSTANT WT. = 0.1



$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$ } METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.

SCALAR INTRODUCED BETWEEN STATIONS AS INDICATED.



STATION NUMBER

FIGURE 28

VARIOUS SIZE NETS

TWO SCALARS CONSTANT WT. = 10^4



$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 29

VARIOUS SIZE NETS

TWO SCALARS CONSTANT WT. = 1.0



$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$ } METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 30

VARIOUS SIZE NETS

TWO SCALARS CONSTANT WT. = 0.1



$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 31

VARIOUS SIZE NETS

THREE SCALARS CONSTANT WT. = 10^4

$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$ } METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 32

VARIOUS SIZE NETS

THREE SCALARS CONSTANT WT. = 1.0

$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$ } METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 33

VARIOUS SIZE NETS

THREE SCALARS CONSTANT WT. = 0.1

$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 34

VARIOUS SIZE NETS

FOUR SCALARS CONSTANT WT. = 10^4

$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS

μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 35

VARIOUS SIZE NETS

FOUR SCALARS CONSTANT WT. = 1.0

$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 36

VARIOUS SIZE NETS

FOUR SCALARS CONSTANT WT. = 0.1

$m_\phi = K_\phi \cdot \mu \cdot 10^7$
$m_\lambda = K_\lambda \cdot \mu \cdot 10^7$
} METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS.



FIGURE 37

VARIOUS SIZE NETS

ONE SCALAR CONSTANT WT. = 10^4

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 38

VARIOUS SIZE NETS

ONE SCALAR CONSTANT WT. = 1.0

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS

——— = K_H ——— = $\sqrt{K_\phi^2 + K_\lambda^2 + K_H^2} = K_{\phi,\lambda,H}$ $M = K_{\phi,\lambda,H} \cdot \mu \cdot 10^7$ METERS



FIGURE 39

VARIOUS SIZE NETS
ONE SCALAR CONSTANT WT. = 0.1

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS

——— = K_H ——— = $\sqrt{K_\phi^2 + K_\lambda^2 + K_H^2} = K_{\phi,\lambda,H}$ $M = K_{\phi,\lambda,H} \cdot \mu \cdot 10^7$ METERS



FIGURE 40

VARIOUS SIZE NETS
TWO SCALARS CONSTANT WT. = 10^4

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS

——— = K_H ——— = $\sqrt{K_\phi^2 + K_\lambda^2 + K_H^2} = K_{\phi,\lambda,H}$ $M = K_{\phi,\lambda,H} \cdot \mu \cdot 10^7$ METERS



FIGURE 41

VARIOUS SIZE NETS
TWO SCALARS CONSTANT WT. = 1.0

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS

——— = K_H ——— = $\sqrt{K_\phi^2 + K_\lambda^2 + K_H^2} = K_{\phi,\lambda,H}$ $M = K_{\phi,\lambda,H} \cdot \mu \cdot 10^7$ METERS



FIGURE 42

VARIOUS SIZE NETS

TWO SCALARS CONSTANT WT. = 0.1

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 43

VARIOUS SIZE NETS
THREE SCALARS CONSTANT WT. = 10^4

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 44

VARIOUS SIZE NETS
THREE SCALARS CONSTANT WT. = 1.0

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 45

VARIOUS SIZE NETS

THREE SCALARS CONSTANT WT. = 0.1

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 46

VARIOUS SIZE NETS
FOUR SCALARS CONSTANT WT. = 10^4

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 47

VARIOUS SIZE NETS

FOUR SCALARS CONSTANT WT. = 1.0

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 48

VARIOUS SIZE NETS

FOUR SCALARS CONSTANT WT. = 0.1

$m_H = K_H \cdot \mu \cdot 10^7$ METERS μ = STANDARD DEVIATION OF UNIT WEIGHT IN MICRONS



FIGURE 49

REFERENCES

1. Schmid, Hellmut H. Reformatory and Revolutionary Aspects in Geodesy. A paper presented at the Meeting of the American Geophysical Union, Washington, D. C., April 22, 1964.

2. Schmid, Hellmut H. Satellite Photogrammetry in Willem Schemerhorn Jubilee Volume, I.T.C., Delft, Netherlands, 1965.

3. Swanson, Lawrence W. Capt. Logistics and Time Schedules for a World Wide Satellite Triangulation Program, U.S. Dept. of Commerce, Coast and Geodetic Survey, Washington, D.C., Mar. 1964.

4. Schmid, Hellmut H. The Method of Passive Satellite Triangulation and its Application by the Coast and Geodetic Survey. U.S. Dept. of Commerce, Coast and Geodetic Survey, Rockville, Md.

5. Schmid, Hellmut H. A General Solution to the Problem of Photogrammetry. Ballistic Research Laboratories Report No. 1065, Aberdeen Proving Ground, Maryland, July 1959.

6. Wooten, Roberta. An Ordvac Program for the Translation of Geodetic Ellipsoidal Coordinates into Cartesian Coordinates and Vice Versa. Ballistic Research Laboratories Memo Report No. 1427, Aberdeen Proving Ground, Maryland, August 1962.

7. Schmid, Hellmut H. and Schmid, Erwin. A Generalized Least Squares Solution for Hybrid Measuring Systems. U.S. Dept. of Commerce, Coast and Geodetic Survey, Rockville, Maryland, June 1965.

8. Schmid, Hellmut H. Precision and Accuracy Considerations for the Execution of Geometric Satellite Triangulation. A paper presented to the Second International Symposium "The Use of Artificial Satellites for Geodesy" at Athens Greece, 1965.

DISTRIBUTION LIST

No. of Copies	Organization
20	Commander Defense Documentation Center ATTN: TIPCR Cameron Station Alexandria, Virginia 22314
1	Assistant Secretary of Defense (R&D) ATTN: Joint Coord Com of GM Washington, D.C. 20301
4	Director of Defense Research & Engineering (OSD) ATTN: Dir/Elct Dir/Ord Dir/GM Washington, D.C. 20301
1	Director Advanced Research Projects Agency ATTN: Plcy & Planning Div Department of Defense Washington, D.C. 20301
1	Chairman Defense Science Board Washington, D.C. 20301
1	Director of Research and Laboratories HQ, U.S. Army Materiel Command Washington, D.C. 20315
1	Commanding General U.S. Army Materiel Command ATTN: AMCRD-RP-B Washington, D.C. 20315
1	Commanding General U.S. Army Materiel Command ATTN: AMCRD-DS Washington, D.C. 20315
2	Commanding General U.S. Army Electronics Command ATTN: AMSEL-BL-D, Meteorological Br. AMSEL-RD, Tech Docu Ctr Fort Monmouth, New Jersey 07703
1	Commanding Officer U.S. Army Electronics Research & Development Activity ATTN: Mr. Durrenberger White Sands Missile Range New Mexico 88002
1	Commanding General U.S. Army Missile Command ATTN: Tech Lib Redstone Arsenal, Alabama 35809
1	Director Redstone Scientific Information Center ATTN: Ch, Docu Sec U.S. Army Missile Command Redstone Arsenal, Alabama 35809
1	Commanding Officer U.S. Army Engineer Research & Development Laboratories ATTN: STINFO Div Fort Belvoir, Virginia 22060
1	President U.S. Air Defense Board Fort Bliss, Texas 79916
1	Commanding General U.S. Army White Sands Missile Range ATTN: ORDBS-TS-TIB White Sands Missile Range New Mexico 88002

DISTRIBUTION LIST

No. of Copies	Organization
3	Commanding Officer U.S. Army Harry Diamond Laboratories Washington, D.C. 20438
2	Commanding Officer U.S. Army Research Office (Durham) ATTN: CRD-AA-IPL Dr. Theodore W. Schmidt Box CM, Duke Station Durham, North Carolina 27706
5	Commanding Officer U.S. Army Map Service ATTN: Col W.H. Van Atta D/Carto Mr. A. Nowicki Mr. J. Theis Mr. J. Webb Corps of Engineers 6500 Brooks Lane Washington, D.C. 20315
5	Commanding Officer U.S. Army Map Service ATTN: Photogrammetric Div Mr. C. Born, D/ESPA Mr. E. Rutscheidt D/GEOD Mr. S. W. Dossi Corps of Engineers 6500 Brooks Lane Washington, D.C. 20315
5	Director U.S. Army Engineer Geodesy, Intelligence & Mapping Research & Development Agency ATTN: Col L. L. Rall Lt Col M. V. Jonah Mr. R. D. Esten Mr. John T. Pennington Mr. D. E. Howell Fort Belvoir, Virginia 22060
1	Superintendent U.S. Naval Observatory ATTN: Dr. William Markowitz 34th & Massachusetts Ave., N.W. Washington, D.C. 20390
1	Commander U.S. Naval Oceanographic Office Washington, D.C. 20390
1	Commander U.S. Naval Reconnaisance & Technical Support Center 4301 Suitland Road Washington, D.C. 20390
3	Chief, Bureau of Naval Weapons ATTN: DLI-3 Department of the Navy Washington, D.C. 20360
2	Commander U.S. Naval Missile Center Point Mugu, California 93041
2	Commander U.S. Naval Ordnance Laboratory White Oak Silver Spring, Maryland 20910
1	Commander U.S. Naval Ordnance Test Station China Lake, California 93557
2	Commander U.S. Naval Weapons Laboratory ATTN: Dr. W. A. Kemper Dr. C. J. Cohen Dahlgren, Virginia 22448
1	Superintendent U.S. Naval Postgraduate School ATTN: Tech Rept Sec Monterey, California 93940

DISTRIBUTION LIST

No. of Copies	Organization
2	Director U.S. Naval Research Laboratory Washington, D.C. 20390
1	HQ USAF (AFCCS-SA) Washington, D.C. 20330
1	ACIC (Mr. Edwin Roth) Second & Arsenal St. Louis, Missouri 63118
1	DET 1 ACIC 1212 S. Fern Street Arlington, Virginia 22202
1	AFSC (SCT) Andrews AFB Washington, D.C. 20331
1	AFFTC (FTOT) Edwards AFB California 93523
1	APGC (Mr. W. A. Brown) Eglin AFB Florida 32542
1	APGC (PGEES) Eglin AFB Florida 32542
1	APGC (PGTRI) Eglin AFB Florida 32542
1	RADC Griffiss AFB New York 13442
2	AFCRL (Geophysics Rsch Div) L. G. Hanscom Fld Bedford, Massachusetts 01731
3	AFMDC (MDS; MDT; MDL) Holloman AFB New Mexico 88330
1	AUL (3T-AUL-60-118) Maxwell AFB Alabama 36112
1	APCS (Capt C. J. Finley) Orlando AFB Florida 31602
2	AFETR (AFETR Tech Lib MU-135 Mr. Obst) Patrick AFB Florida 32925
1	AFAL (AVRP) Wright-Patterson AFB Ohio 45433
1	ARL (ARD) Wright-Patterson AFB Ohio 45433
2	Director P.O. Box 1925 ATTN: James Casey Washington, D.C. 20505
1	Director U.S. Geological Survey ATTN: Mr. Morris M. Thompson 1109 N. Highland Street Arlington, Virginia 22202
1	Director Bureau of Land Management ATTN: Div of Engr, Ch for Cmpt Br. U.S. Department of the Interior 555 Cordova Street Anchorage, Alaska 99501

DISTRIBUTION LIST

No. of Copies	Organization
3	Director Coast & Geodetic Survey ATTN: Mr. William D. Harris LCdr E. A. Taylor Mr. Erwin Schmid U.S. Department of Commerce Washington, D.C. 20230
4	Director Coast & Geodetic Survey ATTN: Capt L. W. Swanson Mr. G. C. Tewinkel Mr. Charles Whitten Mr. L. G. Simmons U.S. Department of Commerce Washington, D.C. 20230
1	Director Geodetic Research Laboratory ESSA-Institute of Earth Sciences ATTN: Dr. Hellmut Schmid U.S. Department of Commerce Rockville, Maryland 20230
1	Director U.S. National Bureau of Standards ATTN: Dr. Irvine C. Gardner 232 Dynamometer Building Washington, D.C. 20235
1	Director U.S. Atomic Energy Commission Sandia Corporation P.O. Box 5800 Sandia Base Albuquerque, New Mexico 87115
1	Director Brookhaven National Laboratory ATTN: O. B. Reading 25 Brookhaven Avenue Upton, New York 11973
4	Director National Aeronautics and Space Administration Goddard Space Flight Center ATTN: Mr. W. M. Kaula Dr. Robert Jastrow Dr. Norberg Dr. John O'Keefe Greenbelt, Maryland 20771
3	Director National Aeronautics and Space Administration Goddard Space Flight Center ATTN: Ch, Theoretical Div Satellite Appl Div Mr. William B. Taylor Greenbelt, Maryland 20771
1	Director Jet Propulsion Laboratory ATTN: Dr. W. Pickering 4800 Oak Grove Drive Pasadena, California 91103
1	Director National Aeronautics and Space Administration ATTN: Mr. R. M. Dickerson Langley Research Center Langley Station Hampton, Virginia 23365
1	Director National Aeronautics and Space Administration George C. Marshall Space Flight Center Huntsville, Alabama 35812
1	Director National Aeronautics and Space Administration ATTN: Mr. Robert Long Wallops Station Wallops Island, Virginia 23337

DISTRIBUTION LIST

No. of Copies	Organization
1	Director National Science Foundation ATTN: Tech Lib Washington, D.C. 20550
2	Director Smithsonian Institute Washington, D.C. 20560
1	Director Smithsonian Astrophysical Observatory ATTN: Dr. Y. Kozai 60 Garden Street Cambridge, Massachusetts 02138
1	President National Academy of Sciences--National Research Council ATTN: Dr. Pembroke J. Hart, Jr. 2101 Constitution Avenue, N.W. Washington, D.C. 20418
1	Applied Physics Laboratory The Johns Hopkins University ATTN: Dr. W. H. Guier 8621 Georgia Avenue Silver Spring, Maryland 20910
1	Aeroflex Laboratories, Inc. ATTN: Engr Sales Mgr 48-25 36th Street Long Island City New York 11101
2	Autometric Corporation ATTN: Mr. E. L. Merritt 4217 Wheeler Avenue Alexandria, Virginia 22314
1	Bausch & Lomb Optical Co. ATTN: Mr. Heinz Gruner 262 St. Paul Street Rochester, New York 14602
1	Bausch & Lomb Incorporated ATTN: Mr. Rex R. McHail Dept G-53 62663 Lamb Park Rochester, New York 14602
1	Cincinnati Observatory ATTN: Dr. Paul Herget Cincinnati, Ohio 45200
1	Control Data Corporation 5630 Arbor Vitae Street Los Angeles, California 90045
1	International Business Machine Corporation Endicott, New York 13760
1	Instrument Corporation of Florida P.O. Box 1226 Melbourne, Florida 32901
2	Kern Instruments, Inc. 120 Grand Street White Plains, New York 10600
2	Lockwood Kessler & Bartlett, Inc. ATTN: Mr. Harold Johnson Mr. Ford Bartlett 1 Aerial Way Syosset, New York 11791
1	Philco Corporation Western Developments Laboratories 3875 Fabian Way Palo Alto, California
1	Ramo-Wooldridge Corporation 5730 Arbor Vitae Street Los Angeles, California 90045

DISTRIBUTION LIST

No. of Copies	Organization
1	RCA Service Company, Inc. ATTN: RCA Data Reduction Gp-Anal Unit Patrick AFB, Florida 32925
1	Technical Operations, Inc. ATTN: Mr. Samuel S. Holland Burlington, Massachusetts 01801
1	Transmares Corporation Minue Street Carteret, New Jersey 07008
3	Wild Heerbrugg Instruments Incorporated ATTN: Mr. K. E. Reynolds Main & Covert Streets Port Washington, New York 11050
1	Carl Zeiss, Incorporated ATTN: Mr. Herbert Trager 445 Fifth Avenue New York, New York 10018
1	Boston University Physical Research Laboratory Boston, Massachusetts 02215
3	Franklin Institute ATTN: Mr. Charles Moench Mr. Charles Belsterling Mr. Anthony Marmarov Benjamin Franklin Pkwy at 20th St. Philadelphia, Pennsylvania 19103
1	Massachusetts Institute of Technology Department of Civil and Sanitary Engineering ATTN: Photogrammetry Lab Mr. C. L. Miller Cambridge, Massachusetts 02139
3	Ohio State University Mapping & Charting Research Laboratory ATTN: Professor Brandberger Professor Heiskanen Columbus, Ohio 43210
1	Princeton University Department of Civil Engineering Princeton, New Jersey 08540
1	Syracuse University Department of Civil Engineering ATTN: Photogrammetric Dept Syracuse, New York 13201
2	University of Maryland Department of Civil Engineering College Park, Maryland 20740
1	Professor P. G. Brennan Department of Civil Engineering Syracuse University Syracuse, New York 13201
1	Professor Arthur Faulds Department of Civil Engineering Syracuse University Syracuse, New York 13201
1	Professor A. J. McNair School of Civil Engineering Cornell University Ithaca, New York 14850
1	Professor M. O. Schmid Department of Civil Engineering University of Illinois Urbana, Illinois 61803
1	Professor Edward Young University of Michigan Ann Arbor, Michigan 48014

DISTRIBUTION LIST

No. of Copies	Organization
1	Dr. Dirk Brouwer Yale University Observatory New Haven, Connecticut 06511
1	Dr. R. H. Dicke Palmer Physical Laboratory Princeton University Princeton, New Jersey 08540
1	Dr. W. M. Ewing Lamount Geological Laboratory University of New York New York, New York
1	Dr. George Gardiner School of Agriculture and Mechanic Arts New Mexico State University State College, New Mexico
1	Dr. H. M. Karara Department of Civil Engineering University of Illinois Urbana, Illinois 61803
1	Dr. G. J. F. MacDonald Institute of Geophysics and Planetary Physics University of California Los Angeles, California 90024
2	Dr. Fred Whipple Smithsonian Astrophysical Observatory 60 Garden Street Cambridge, Massachusetts 02138
1	Mr. V. A. Van Praag 3861 Mount Vernon Drive Los Angeles, California 90008
5	Mr. Marshall S. Wright, Sr. Ashlawn 1129 4921 Seminary Road Alexandria, Virginia 22311
	Aberdeen Proving Ground
	Ch, Tech lib
	Air Force Ln Ofc Marine Corps Ln Ofc Navy Ln Ofc CDC Ln Ofc

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)	2a. REPORT SECURITY CLASSIFICATION
U.S. Army Ballistic Research Laboratories Aberdeen Proving Ground, Maryland	Unclassified
	2b GROUP

3. REPORT TITLE

ERROR STUDY OF A WORLDWIDE SATELLITE TRIANGULATION NET

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

5. AUTHOR(S) *(Last name, first name, initial)*

Lortie, Edna L.

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
January 1966	79	8

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)
b. PROJECT NO. RDT&E 1L013001A91A	Report No. 1310
c.	9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)*
d.	

10. AVAILABILITY/LIMITATION NOTICES

Distribution of this document is unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	U.S. Army Materiel Command Washington, D.C.

13. ABSTRACT

A proposed three-dimensional geodetic reference system, consisting of 36 stations so situated on the surface of the earth as to form a closed system of approximate equilateral triangles surrounding the globe, is studied in an attempt to find out to what degree of accuracy the station positions can be determined when triangulating the corresponding station coordinates by photogrammetric techniques. The polyhedron of the spatially oriented triangles is formed by photographing a high altitude satellite against the star background. The triangulation method depends on applying analytical photogrammetric techniques to satellite observations where the satellite serves as a high altitude auxiliary triangulation target point. Numerical analyses on the whole net and portions of it are presented from which the problem of error propagation and the influence of the number of baselines can be studied.

DD FORM 1 JAN 64 1473

Unclassified

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Error analysis Worldwide reference system Geodetic triangulation Photogrammetry Satellites						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2*a*. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2*b*. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7*a*. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7*b*. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8*a*. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8*b*, 8*c*, & 8*d*. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9*a*. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9*b*. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS)*, *(S)*, *(C)*, *or (U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Idenfiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.